

	J3C S20	J3C S35	J3C S55	J3C S85
Spannungsbereich/ voltage	24 - 240 V AC/DC			
Losbrechdrehmoment/ break torque	25 Nm	38 Nm	60 Nm	90 Nm
Arbeitsdrehmoment/ operational torque	20 Nm	35 Nm	55 Nm	85 Nm
Einschaltdauer/ duty rating (ED)	75%	75%	75%	75%
Schutzart/ protection class	IP67	IP67	IP67	IP67
Temperaturbereich/ temperature range	-20°C bis 70°C / -4°F to 158°F			
Flansch/ flange	F03/F04/F05 F07 via Kit	F03/F04/F05 F07 via Kit	F05/F07	F05/F07
Achtkant/ double square alternatives	9 mm, 11 mm, 14 mm	9 mm, 11 mm, 14 mm	14 mm, 17 mm	14 mm, 17 mm
Anschluss/ connectors	DIN EN 175301 - 803			
Rückmeldung/ feedback signal	2 potentialfreie Mikroschalter / 2 volt free contact micros: (SPST) 5 A 125 V AC / 3 A 250 V AC			
Drehmomentabschaltung/ torque limiter	x	x	x	x
Heizung/ heater	3,5 W	3,5 W	3,5 W	3,5 W
Gehäuse/ housing	Polyamid / Polyamide (PA6)			
Gewicht/ weight	1,9 kg	1,9 kg	2,4 kg	3,0 kg