


VULKOLLAN® Laufräder



Serie 178



Artikelcode	mm	mm	mm	mm	mm	mm	kg
178/100/025/5/15	100	25	25	26	43	15	200
178/100/035/5/12	100	35	40	40	42	12	300
178/100/040/5/15 B*	100	40	45	42	45	15	350
178/100/040/5/15	100	40	45	42	45	15	350
178/100/040/5/25	100	40	45	45	54	25	350
178/100/050/5/20 B*	100	50	50	54	-	20	450
178/100/050/5/25-1	100	50	50	54	-	25	450
178/100/050/5/25-2	100	50	50	48	-	25	450
178/125/040/5/15	125	40	45	45	42	15	450
178/125/040/5/20	125	40	45	43	60	20	450
178/125/050/5/20	125	50	50	54	59	20	560
178/125/050/5/25-1	125	50	50	54	59	25	560
178/125/050/5/25-2	125	50	50	48	59	25	560
178/125/070/5/25	125	70	70	74	65	25	660
178/150/035/5/25	150	35	35	39	62	25	450
178/150/050/5/20	150	50	50	54	61	20	660
178/150/050/5/25-1	150	50	50	54	61	25	660
178/150/050/5/25-2	150	50	50	48	61	25	660
178/150/080/5/25	150	80	72	78	65	25	900
178/160/040/5/20	160	40	45	49	61	20	550
178/160/050/5/20	160	50	60	60	65	20	700
178/160/050/5/25	160	50	50	48	70	25	600
178/180/050/5/25	180	50	50	48	66	25	800
178/200/050/5/20	200	50	60	64	65	20	1.000
178/200/050/5/25	200	50	60	64	65	25	1.000
178/200/050/5/30	200	50	50	48	86	30	840
178/200/080/5/25-1	200	80	80	84	70	25	1.400
178/200/080/5/25-2	200	80	78	78	95	25	1.400
178/200/080/5/30	200	80	78	85	80	30	1.400
178/200/080/5/35	200	80	80	78	82	35	1.450
178/250/050/5/25	250	50	60	64	67	25	1.100
178/250/050/5/30	250	50	50	48	83	30	1.100
178/250/060/5/25	250	60	60	60	77	25	1.350
178/250/080/5/30-1	250	80	80	80	75	30	1.700
178/250/080/5/30-2	250	80	78	78	91	30	1.800
178/250/080/5/40	250	80	80	78	101	40	1.800
178/300/060/5/30	300	60	65	65	82	30	1.600
178/300/080/5/40	300	80	85	85	106	40	2.100
178/300/100/5/50	300	100	100	100	105	50	2.750
178/300/135/5/90	300	135	135	135	140	50	3.400
178/400/075/5/45	400	75	80	80	131	45	2.200
178/400/100/5/50	400	100	100	100	130	50	3.660
178/500/085/5/90	500	85	100	100	140	50	2.360
178/500/200/5/90	500	200	200	200	230	90	9.170

* mit balliger Lauffläche

VULKOLLAN® Antriebsräder

Serie 178 A



Artikelcode	mm	mm	mm	mm	mm	mm	kg
178 A/100/050/2/25 H7	100	50	50	-	25	450	
178 A/125/040/2/20 H7	125	40	36	46	20	450	
178 A/125/040/2/25 H7	125	40	45	60	25	450	
178 A/125/050/2/25 H7	125	50	50	60	25	560	
178 A/125/050/2/30 H7	125	50	50	60	30	560	
178 A/125/050/2/35 H7	125	50	50	60	35	560	
178 A/150/050/2/30 H7	150	50	50	61	30	650	
178 A/150/050/2/35 H7	150	50	50	61	35	650	
178 A/160/050/2/40 H7	160	50	50	61	40	660	
178 A/160/050/2/25 H7	160	50	50	61	25	700	
178 A/160/050/2/35 H7	160	50	50	61	35	700	
178 A/180/055/2/35 H7	180	55	60	63	35	850	
178 A/200/050/2/30 H7	200	50	60	65	30	1.000	
178 A/200/050/2/35 H7	200	50	60	65	35	1.000	
178 A/200/050/2/40 H7	200	50	60	85	35	1.000	
178 A/250/050/2/30 H7	250	50	60	85	40	1.000	
178 A/250/050/2/40 H7	250	50	60	90	50	1.400	
178 A/250/050/2/50 H7	250	50	50	90	40	1.100	
178 A/250/080/2/30 H7	250	80	80	90	30	1.800	
178 A/250/080/2/40 H7	250	80	80	100	40	1.800	
178 A/250/080/2/50 H7	250	80	80	100	40	1.800	
178 A/300/060/2/40 H7	300	60	65	82	40	1.600	
178 A/300/060/2/50 H7	300	60	65	80	50	1.600	
178 A/300/080/2/50 H7	300	80	80	107	50	2.100	
178 A/300/100/2/40 H7	300	100	100	106	40	2.500	
178 A/300/100/2/60 H7	300	100	110	105	60	2.500	

VULKOLLAN® Antriebsräder
Redkörper aus Grauguss mit Passbohrung und Nut nach DIN 6885. Fest aufgegossener VULKOLLAN® Lauffbelag (93° Shore A).