

Indication of L-Series Motor

Model	Frame	Output	Ratio	Voltage	Accessory
J220 Vertical Motor(For Carton Sealer only) LH Horizontal Aluminum Alloy Gear Motor LV Vertical Aluminum Alloy Gear Motor	18 : Frame 18 22 : Frame 22 28 : Frame 28 32 : Frame 32 40 : Frame 40 50 : Frame 50	100 : 100W(1/8HP) 200 : 200W(1/4HP) 400 : 400W(1/2HP) 750 : 750W(1HP) 1500 : 1500W(2HP) 2200 : 2200W(3HP) 3700 : 3700W(5HP)	3-1800	AC : 1 Phase110/220V AV : 1 Phase110/220V AVE : 1 Phase110/220V CE : 1 Phase 120/240V S3 : 3 Phase 220/380V S4 : 3 Phase 220/440V S7 : 3 Phase 230/415V	M : Electromagnetic Brake

Terminal Box Direction

Type	G1-Left Side (Standard Type)	G2-Right Side	G3-Upper Side	G4-Lower Side
LH				
LV				
Wire Inlet Direction	LD LT RD RT	TL TR DL DR	LF LB RF RB	TF TB DF DB

* Please contact us while the motor is running under the low temperature environment.