



## SCREWED END GATE • GLOBE • CHECK • NEEDLE VALVES AND STRAINERS

### GATE VALVES GT-200



#### Design Feature

- 1/2" – 2" (DN15 - DN50)
- Non-Rising stem, solid disc

Body / Disc	ASTM A351 Gr.CF8M (EN1.4408)
Packing	PTFE
Working Pressure	200 PSI / PN16
End Connection	Threaded end

### GLOBE VALVES GB-200



#### Design Feature

- 1/4" – 2" (DN8 - DN50)
- Rising stem, solid disc

Body / Disc	ASTM A351 Gr.CF8M (EN1.4408)
Packing	PTFE
Working Pressure	200 PSI / PN16
End Connection	Threaded end

### STRAINERS YS-800



#### Design Feature

- 1/4" – 3" (DN8 - DN80)
- Y-type Strainer

Body	ASTM A351 Gr.CF8M (EN1.4408)
Screen / Packing	SS316 / PTFE
Working Pressure	800 PSI / PN40
End Connection	Threaded end

### GLOBE YGB-800



#### Design Feature

- 1/4" – 3" (DN8 - DN80)
- Rising stem, solid disc

Body / Disc	ASTM A351 Gr.CF8M (EN1.4408)
Packing	PTFE
Working Pressure	800 PSI / PN40
End Connection	Threaded end

### CHECK VALVES SC-200



#### Design Feature

- 1/4" – 3" (DN8 - DN80)
- Swing type

Body / Disc	ASTM A351 Gr.CF8M (EN1.4408)
Body seal	PTFE
Working Pressure	200 PSI / PN16
End Connection	Threaded end

### CHECK VALVES YSP-800



#### Design Feature

- 1/4" – 2" (DN8 - DN50)
- Y type Spring type

Body / Disc	ASTM A351 Gr.CF8M (EN1.4408)
Spring	SS316
Working Pressure	800 PSI / PN40
End Connection	Threaded end

### CHECK VALVES WA-002



#### Design Feature

- 1/4" – 4" (DN8 - DN100)
- 3 pieces
- Spring type

Body / Disc	ASTM A351 Gr.CF8M (EN1.4408)
Body seal	PTFE
Working Pressure	800 PSI / PN40
End Connection	Threaded end, Socket weld, Butt weld end

### NEEDLE VALVES



NV-0060

NV-0061

NV-0062

NV-0063

- NV-0060 NV-0062 Female X Female screwed end
- NV-0061 NV-0063 Male X Female screwed end
- 1/8" ~1" (DN8 ~ DN25)
- CWP : 6000 psi
- Body : SS 316 ( Investment casting )